

SABdrain

water drainage systems

351 100mm x 50mm - Load Class A10

FOR CONCRETE

Specification Clause

The surface drainage system shall be Sabdrain 351 100 100 polypropylene plastic channel, fitted with polypropylene grating Load Class - A10.

Properties

Sabdrain 351 10050 polypropylene plastic channels shall meet the following properties:-

| | |
|-------------------------------|---------------------------|
| COMPRESSIVE STRENGTH | 58N/mm ² |
| TENSILE STRENGTH | 14N/mm ² |
| DENSITY | 0.960 g/cm ³ |
| WATER ABSORPTION | <0.05% |
| THERMAL EXPANSION COEFFICIENT | 15x12 ⁻⁵ mm/°C |
| FROST PROOF | YES |
| MELTING POINT | 162 – 168 °C |
| CO EFFICIENT OF ROUGHNESS | N=0.010 |
| CHEMICAL RESISTENCE | YES |
| NON FLAMMABLE | YES |

for detailed chemical resistance, refer to <https://sabdrain.com.au/chemical-resistance/>

Dimensions

Sabdrain 351 10050 channels dimensions shall be an internal height of 50mm with an internal width of 100mm and an overall height of 100mm and width of 150mm, with Male/Female interlocking joints, the channels shall have provision to create a 2° (17M) Radius.


Grates

Refer to the relevant specification sheet for the selected grate.

Installation

The Sabdrain 351 10050 Drainage system shall be installed for its intended purpose. Any improper installation and usage could result in product failure.

Expansion Joint to Engineers Specification. (See Note 3)



Notes

1. Concrete encasement dimensions and/or reinforcement changes may be required for specific site conditions. Minimum concrete strength of 25MPa is recommended. Ensure concrete is vibrated Alwaysseek engineering advice.
2. The finished level of the concrete encasement should be 3-5mm above the channel edge.
3. Expansion control joints are recommended for protection of the concrete encasement.

