



Specification Clause

The surface drainage system shall be SABdrain 602 100 100 polypropylene plastic channel, fitted with galvanised steel grating Load Class – B80. (Load Classification AS3996:2006 B80 is similar to EN1433:2008 B125.)

Properties

SABdrain 602 100100 polypropylene plastic channels shall meet the following properties:

COMPRESSIVE STRENGTH	58N/mm ²
TENSILE STRENGTH	14N/mm ²
DENSITY	0.960 g/cm ³
WATER ABSORPTION	<0.05%
THERMAL EXPANSION COEFFICIENT	15x12 ⁻⁵ mm/°C
FROST PROOF	YES
MELTING POINT	162 – 168 °C
CO EFFICIENT OF ROUGHNESS	N=0.010
CHEMICAL RESISTANCE	YES
NON FLAMMABLE	YES

for detailed chemical resistance, refer to sabdrain.com.au/chemical-resistance/

Dimensions

SABdrain 602 100100 channels dimensions shall be an internal height of 100mm with an internal width of 100mm and an overall height of 150mm and width of 150mm, with Male/Female interlocking joints, the channels shall have provision to create a 2° (17M) Radius.

Grates

Refer to the relevant specification sheet for the selected grate.

Installation

The SABdrain 602 100100 Drainage system shall be installed for its intended purpose. Any improper installation and usage could result in product failure.

Notes

- Concrete encasement dimensions and/or reinforcement changes may be required for specific site conditions. Minimum concrete strength of 25MPa is recommended. Ensure concrete is vibrated. Always seek engineering advice.
- The finished level of the concrete encasement should be 3-5mm above the channel edge.
- Expansion control joints are recommended for protection of the concrete encasement.